

## Locking Handle Bronze Ball Valves


**Application:**

- for control of air, water, oil and gas in hose or pipe lines, for other services, please contact Dixon®

**Features:**

- pressure rating: **600 PSI WOG**; **150 PSI** saturated steam
- blow-out proof RPTFE stem
- chrome-plated bronze ball
- Stainless steel sliding lock mechanism secures handle in open or closed position; can be padlocked opened or closed.
- plated steel handles and nuts with vinyl sleeves
- full and standard port valves are repairable

Female NPT	Port	Bronze Part #
1/4"	full	<b>BBLV25</b>
3/8"	full	<b>BBLV38</b>
1/2"	full	<b>BBLV50</b>
3/4"	standard	<b>BBLV75</b>
1"	standard	<b>BBLV100</b>
1 1/4"	standard	<b>BBLV125</b>
1 1/2"	standard	<b>BBLV150</b>
2"	standard	<b>BBLV200</b>



Valves

## Bronze Ball Valves

**Applications:**

- for air, water, oil and gas service

**Features:**

- pressure rating: **600 PSI**, cold non-shock pressure rating: **150 PSI** saturated steam
- chromium plated ball
- RTFE seats and stuffing box ring
- blow-out proof stem
- adjustable packing gland

Male NPT x Female NPT	Port	Bronze Part #
1/2"	standard	<b>BMV50</b>
3/4"	standard	<b>BMV75</b>
1"	standard	<b>BMV100</b>



## "Deadman" Spring Return Handle Brass Ball Valves

**Features:**

- pressure rating: **600 PSI WOG**; **150 PSI** saturated steam
- vacuum service to 29 inches Hg
- stainless steel lever
- chromium plated ball
- RTFE seats and stuffing box ring
- blow-out proof stem design
- adjustable packing gland
- spring return closes valve when not held open
- operating torque approximately three times standard valve torque

Female NPT	Port	Brass Part #
1/2"	full	<b>BBV50SR</b>
3/4"	standard	<b>BBV75SR</b>
1"	standard	<b>BBV100SR</b>
1 1/2"	standard	<b>BBV150SR</b>
2"	standard	<b>BBV200SR</b>

