

3-Piece Industrial Stainless Steel Ball Valves FNPT

Features:

- blow out proof stem
- live-loaded stem packing
- swing out design for easy maintenance
- ISO 5211 mounting pad
- RTFE seat and seals
- maximum temperature: **400°F (200°C)**
- maximum pressure: 1/4" - 1/2" **1,000 PSI** WOG at 65°F, 2 1/2" - 3" **800 PSI** WOG at 65°F, 4" **600 PSI** WOG at 65°F

Female NPT	Port	PSI @ 65°F	Body Length	CF8M Stainless Steel Part #
1/2"	full	1000	2.8"	BV2IGN05011-A
3/4"	full	1000	3.1"	BV2IGN07511-A
1"	full	1000	3.3"	BV2IGN10011-A
1 1/4"	full	1000	4.1"	BV2IGN12511-A
1 1/2"	full	1000	4.4"	BV2IGN15011-A
2"	full	1000	5.1"	BV2IGN20011-A
2 1/2"	full	800	6.6"	BV2IGN25011-A
3"	full	800	7.3"	BV2IGN30011-A
4"	full	600	8.9"	BV2IGN40011-A



Valves

3-Piece Industrial Stainless Steel Ball Valves Socket Weld

Female NPT	Port	PSI @ 65°F	Body Length	CF8M Stainless Steel Part #
1/2"	full	1000	2.8"	BV2IGN05033-A
3/4"	full	1000	3.1"	BV2IGN07533-A
1"	full	1000	3.3"	BV2IGN10033-A
1 1/4"	full	1000	4.1"	BV2IGN12533-A
1 1/2"	full	1000	4.4"	BV2IGN15033-A
2"	full	1000	5.1"	BV2IGN20033-A
2 1/2"	full	800	6.6"	BV2IGN25033-A
3"	full	800	7.3"	BV2IGN30033-A
4"	full	600	8.9"	BV2IGN40033-A



"Deadman" Spring Return Handle Stainless Steel Ball Valves

Features:

- pressure rating: **2000 PSI** WOG 1/2" to 1"; **1500 PSI** WOG 1 1/4" to 2"
- **150 PSI** saturated steam, all sizes
- vacuum service to 29 inches Hg, all sizes
- PTFE seal
- blow-out proof stem design
- adjustable packing gland
- spring return closes valve when not held open
- operating torque approximately three times standard valve torque

Female NPT	Port	316 Stainless Steel Part #
1/2"	full	SSBV50SR
3/4"	standard	SSBV75SR
1"	standard	SSBV100SR
1 1/4"	standard	SSBV125SR
1 1/2"	standard	SSBV150SR
2"	standard	SSBV200SR

