

Flow Control Valves

Steel Series N

Features:

- excellent speed control on hydraulic systems where a reverse flow check valve is not needed
- reliable shutoff in a very small envelope; color-coded reference scale simplifies setting, resetting, adjusting and quick return to a previous speed setting
- maximum operating pressure: **5000 PSI at 70°F (21°C)** for 1/8" - 3/4", **3000 PSI at 70°F (21°C)** for 1" - 1 1/4"

Female NPTF	Steel Part #
1/8"	<b>SN200</b>
1/4"	<b>SN400</b>
3/8"	<b>SN600</b>
1/2"	<b>SN800</b>
3/4"	<b>SN1200</b>
1"	<b>SN1600</b>
1 1/4"	<b>SN2000</b>



Valves

Brass Series N

Features:

- for use as speed control on hydraulic and pneumatic systems where a reverse flow check valve is not needed
- provides excellent control and reliable shutoff in a very small envelope
- color coded scale simplifies setting, resetting, adjusting and quick return to a previous speed setting
- maximum operating pressure: **2000 PSI** at ambient temperature **70°F (21°C)** for sizes 1/8" - 3/4", **500 PSI** at ambient temperature **70°F (21°C)** for 1"

Female NPTF	Brass Part #
1/8"	<b>BN200</b>
1/4"	<b>BN400</b>
3/8"	<b>BN600</b>
1/2"	<b>BN800</b>
3/4"	<b>BN1200</b>
1"	<b>BN1600</b>

