Hydraulic Adapters - Flareless Bite Fittings

Applications

- Chemical, pulp and paper, oil and gas refineries, military, air compressors, and machine tools
- Well-suited for a variety of processing and general hydraulic applications

Features

- Ideally suited for use with tubing having medium to extra heavy wall thicknesses
- 3-piece design with only one ferrule eliminates possible make-up errors that may occur using a twin ferrule tube fitting
- Minimal risk of improper assembly as the ferrule visibly bites into the tubing, allowing installer to visually inspect the bite quality
- Fittings are suitable for sub-zero through elevated temperature applications

Specifications

- Temperature rating is limited by the material chosen
- Pressure ratings are determined by the size (O.D.) and wall thickness (inches/mm) of the tubing on which they are to be installed

Approval

• Exceeds Military (MIL F18866) and SAE J514 standards

Assembly Instructions

- · Cut, deburr and clean tubing
- Pre-set ferrule onto tubing
- Inspect ferrule bite in tubing by disassembling the fitting and visually inspecting the deburred end of tube for slight indentation
- Finger tighten nut and then further wrench tighten nut another 1/3 to 1/2 turn

Male Tube x Male NPTF Adapters

| | | • |
|-----------|-----------|-----------------|
| Tube O.D. | Male NPTF | Steel Part # |
| 1/8" | 1/8" | FLC2404-02 |
| | 1/4" | FLC2404-02-04 |
| 3/16" | 1/8" | FLC2404-03-02 |
| · | 1/8" | FLC2404-04-02 |
| 7 / 4!! | 1/4" | FLC2404-04 |
| 1/4" | 3/8" | FLC2404-04-06 |
| | 1/2" | FLC2404-04-08 |
| F /1 C!! | 1/8" | FLC2404-05-02 |
| 5/16" | 1/4" | FLC2404-05-04 |
| | 1/8" | FLC2404-06-02 |
| 0 (0) | 1/4" | FLC2404-06-04 |
| 3/8" | 3/8" | FLC2404-06 |
| | 1/2" | FLC2404-06-08 |
| | 1/4" | FLC2404-08-04 |
| 1 (0) | 3/8" | FLC2404-08-06 |
| 1/2" | 1/2" | FLC2404-08 |
| | 3/4" | FLC2404-08-12 |
| | 3/8" | FLC2404-10-06 |
| 5/8" | 1/2" | FLC2404-10-08 |
| | 3/4" | FLC2404-10-12 |
| | 1/2" | FLC2404-12-08 |
| 3/4" | 3/4" | FLC2404-12 |
| • | 1" | FLC2404-12-16 |
| | 3/4" | FLC2404-16-12 |
| 1" | 1" | FLC2404-16 |
| | 1-1/4" | FLC2404-16-20 |
| 1 1 / 4" | 3/4" | FLC2404-20-12 |
| 1-1/4" | 1-1/4" | FLC2404-20 |
| 1-1/2" | 1-1/2" | FLC2404-24 |



Male Tube x Male 37° JIC

| Tube O.D. | Male 37° JIC | Steel Part # |
|-----------|--------------|-----------------|
| 1/4" | 1/4" | FLC2402-04-04 |
| 3/8" | 3/8" | FLC2402-06-06 |
| 1/2" | 1/2" | FLC2402-08-08 |
| 3/4" | 3/4" | FLC2402-12-12 |



K