## **Turbo Nozzles**

- Features20° spray angle
- Ceramic orifice

### Specification

• Maximum temperature: 212°F (100°C)



AL414

AL416

Nozzle Size	Description	Orifice	Maximum Working PSI	Part #
4.0	1/4" female inlet	1.30 mm	3,700	AL-TPR25-30
6.0	1/4" female inlet	1.50 mm	3,700	AL-TPR25-50
7.0	1/4" female inlet	1.70 mm	3,700	AL-TPR25-70
4.0	1/4" female inlet	1.30 mm	5,075	AL-TPR35-30
6	1/4" female inlet	1.50 mm	5,075	AL-TPR35-50
7	1/4" female inlet	1.70 mm	5,075	AL-TPR35-70

# **Nozzle Holders**

### Specification

Maximum temperature: 320°F (160°C)

Description	Flow (GPM)	Working PSI	Part #
adjustable hi/low nozzle holder with nozzle protector, 1/4" female inlet and outlet	8	3,650	AL414
change over nozzle, 1/4" female inlet, 2 each 1/4" female outlets	8	2,900	AL416

# **Inlet Filter for Turbo Nozzles**

- Features1/4" female inlet, 1/4" male outlet
- 100 mesh filter

### Specification

Maximum temperature: 212°F (100°C)

Description	Flow (GPM)	Working PSI	Part #
stainless steel, inlet water filter	8	5,000	AR3500

# **Balance Release Valve**

### Features

- Inlet/outlet: 3/8" female NPT
- Bypass: 3/8" female NPT

### Specifications

- Working PSI: 4,000 PSI
- Maximum temperature: 195°F (90.6°)
- GPM: 6.6

### Brass Part #

AL702

## Water Broom

- Features
- 1/4" quick connect plug

### Specification

• Working PSI: 4,000 PSI

Description	Length	Stainless Steel Part #	
4-nozzle broom	16"	AR-BROOM16	



