

Safety Vented Ball Valves

Application

For air service only

Features

- · Blow-out proof stem design
- Adjustable packing gland

Specification

• Pressure rating: 0-125 PSI

Approval

 Vent downstream air in accordance with OSHA regulation 1910.147 for pneumatic systems



Materials

- Bronze valve
- · Chromium plated ball
- · RTFE seats and stuffing box ring

| Female NPT | Port | Required Case Qty | Bronze Part # |
|------------|----------|-------------------|------------------|
| 3/4" | standard | 3 | BBV75LV |

NOTE: Products placed in blue plastic bin with label.

Whip Hose

| Description | Required Case Qty | Part # |
|---|-------------------|--------------|
| Whip hose 1/2" x 6', Air King x 7/8" threaded bent stem | 1 | WH50X6AKBS87 |



| Description | Required Case Qty | Part # |
|---|-------------------|--------------|
| Whip hose 1/2" x 6', Air King x 1/2" threaded bent stem | 1 | WH50X6AKBS50 |



| Description | Required Case Qty | Part # |
|---|-------------------|------------|
| Whip hose 3/4" x 6', Air King x 3500 nipple | 1 | WH75X6AK35 |



Sign Holder

| Description | Required Case Qty | Part # | |
|---------------------|-------------------|------------|--|
| end cap sign holder | 2 | SIGNHOLDER | |



End Cap Sign

| Description | Required Case Qty | Part # | |
|--------------------------|-------------------|---------|--|
| Outside air end cap sign | 1 | OA-SIGN | |



Blue Bins with Label

| Description | Required Case Qty | Contents | Part # |
|----------------------|-------------------|--|-------------|
| Blue bins with label | 1 | S-12416 (2), S-13536 (13), S-12414 (5) | OA-BLU-BINS |



