

## K-Series Hydraulic Couplings

## Features:

- poppet style shut-off valves in both coupler and plug
- interchangeable with Aeroquip/Eaton FD56 (5600), Parker 6600, and **ISO-A 7241 interchange**, see Hydraulic Profile Chart on page 460
- nitrile (Buna-N) seal standard, providing a temperature range of **-40°F to 250°F (-40°C to 121°C)**
- Contact Dixon® for additional seal material options, pressure ratings and other technical information.

## ISO-A Interchange Female Threaded Couplers

Body Size	Threads	Previous Part #	Steel Part #	316 Stainless Steel Part #
1/4"	1/8" - 27 NPTF	56-100	<b>2KF1</b>	---
	1/4" - 18 NPTF	56-200	<b>2KF2</b>	<b>2KF2-SS</b>
	1/4" - 19 BSPP	---	<b>2KBF2</b>	<b>2KBF2-SS</b>
	7/16" - 20 ORB	---	<b>2KOF2</b>	---
3/8"	3/8" - 18 NPTF	56-300	<b>3KF3</b>	<b>3KF3-SS</b>
	3/8" - 19 BSPP	---	<b>3KBF3</b>	<b>3KBF3-SS</b>
	9/16" - 18 ORB	---	<b>3KOF3</b>	---
1/2"	1/2" - 14 NPTF	56-400	<b>4KF4</b>	<b>4KF4-SS</b>
	1/2" - 14 BSPP	---	<b>4KBF4</b>	<b>4KBF4-SS</b>
	3/4" - 16 ORB	---	<b>4KOF4</b>	---
	7/8" - 14 ORB	---	<b>4KOF5</b>	---
	3/4" - 14 NPTF	56-600	<b>4KF6</b>	---
3/4"	3/4" - 14 NPTF	56-660	<b>6KF6</b>	<b>6KF6-SS</b>
	3/4" - 14 BSPP	---	<b>6KBF6</b>	<b>6KBF6-SS</b>
1"	1-1/16" - 12 ORB	---	<b>6KOF6</b>	---
	1" - 11 1/2 NPTF	56-800	<b>8KF8</b>	<b>8KF8-SS</b>
	1" - 11 BSPP	---	<b>8KBF8</b>	<b>8KBF8-SS</b>
1 1/4"	1-5/16" - 12 ORB	---	<b>8KOF8</b>	---
	1 1/4" - 11 1/2 NPT	---	<b>10KF10</b>	---
1 1/2"	1 1/4" - 11 BSPP	---	<b>10KBF10</b>	---
	1 1/2" - 11 1/2 NPT	---	<b>12KF12</b>	---
2"	1 1/2" - 11 BSPP	---	<b>12KBF12</b>	---
	2" - 11 1/2 NPT	---	<b>16KF16</b>	---
2"	2" - 11 BSPP	---	<b>16KBF16</b>	---



4KF4 - steel




4KF6 - steel



10KF10 - steel

## ISO-A Interchange Female Threaded Plugs

Body Size	Threads	Previous Part #	Steel Part #	316 Stainless Steel Part #
1/4"	1/8" - 27 NPTF	57-100	<b>K2F1</b>	---
	1/4" - 18 NPTF	57-200	<b>K2F2</b>	<b>K2F2-SS</b>
	1/4" - 19 BSPP	---	<b>K2BF2</b>	<b>K2BF2-SS</b>
	7/16" - 20 ORB	---	<b>K2OF2</b>	---
3/8"	3/8" - 18 NPTF	57-300	<b>K3F3</b>	<b>K3F3-SS</b>
	3/8" - 19 BSPP	---	<b>K3BF3</b>	<b>K3BF3-SS</b>
	9/16" - 18 ORB	---	<b>K3OF3</b>	---
1/2"	1/2" - 14 NPTF	57-400	<b>K4F4</b>	<b>K4F4-SS</b>
	1/2" - 14 BSPP	---	<b>K4BF4</b>	<b>K4BF4-SS</b>
	3/4" - 16 ORB	---	<b>K4OF4</b>	---
	7/8" - 14 ORB	---	<b>K4OF5</b>	---
	3/4" - 14 NPTF	57-600	<b>K4F6</b>	---
3/4"	3/4" - 14 NPTF	57-660	<b>K6F6</b>	<b>K6F6-SS</b>
	3/4" - 14 BSPP	---	<b>K6BF6</b>	<b>K6BF6-SS</b>
1"	1-1/16" - 12 ORB	---	<b>K6OF6</b>	---
	1" - 11 1/2 NPTF	57-800	<b>K8F8</b>	<b>K8F8-SS</b>
	1" - 11 BSPP	---	<b>K8BF8</b>	<b>K8BF8-SS</b>
1 1/4"	1-5/16" - 12 ORB	---	<b>K8OF8</b>	---
	1 1/4" - 11 1/2 NPT	---	<b>K10F10</b>	---
1 1/2"	1 1/4" - 11 BSPP	---	<b>K10BF10</b>	---
	1 1/2" - 11 1/2 NPT	---	<b>K12F12</b>	---
2"	1 1/2" - 11 BSPP	---	<b>K12BF12</b>	---
	2" - 11 1/2 NPT	---	<b>K16F16</b>	---
2"	2" - 11 BSPP	---	<b>K16BF16</b>	---



K4F4 - steel



K6F6 - steel