

## Dual-Lock™ P-Series Pneumatic Couplings

**Features:**

- interchanges with National A type, Campbell Double-Lock and Thor PHC series couplings
- spring loaded interlocking engagement
- optional locking key prevents sleeve retraction
- working pressure: **300 PSI** at ambient temperature **70°F (21°C)**
- Nitrile (Buna-N) seals are standard temperature range **-40°F to 250°F (-40°C to 121°C)**
- steel componentry is plated using ROHS compliant trivalent chrome

### Female Thread Couplers

Body Size	Threads	Brass		Steel		303 Stainless Steel	
		Previous Part #	Part #	Previous Part #	Part #	Previous Part #	Part #
1/2"	3/8" - 14 NPTF	---	---	PFL8	<b>4PF4</b>	---	---
	3/4" - 14 NPTF	---	<b>4PF6-B</b>	PFL12	<b>4PF6</b>	PFL12SS	<b>4PF6-S</b>



brass



steel



303 stainless

### Female Thread Plugs

Body Size	Threads	Brass		Steel		303 Stainless Steel	
		Previous Part #	Part #	Previous Part #	Part #	Previous Part #	Part #
1/2"	3/8" - 18 NPTF	---	---	PF6	<b>P4F3</b>	---	---
	1/2" - 14 NPTF	PFB8	<b>P4F4-B</b>	PF8	<b>P4F4</b>	---	---
	3/4" - 14 NPTF	PFB12	<b>P4F6-B</b>	PF12	<b>P4F6</b>	PF12SS	<b>P4F6-S</b>
	3/4" - 14 NPTF	---	---	---	<b>P4F6-9<sup>1</sup></b>	---	---
	1" - 11 1/2 NPTF	PFB16	<b>P4F8-B</b>	PF16	<b>P4F8</b>	---	---

<sup>1</sup> steel/PTFE coating



brass



steel



303 stainless

### Male Thread Couplers

Body Size	Threads	Steel		303 Stainless Steel	
		Previous Part #	Part #	Previous Part #	Part #
1/2"	3/8" - 18 NPTF	PML6	<b>4PM3</b>	---	---
	1/2" - 14 NPTF	PML8	<b>4PM4</b>	---	---
	3/4" - 14 NPTF	PML12	<b>4PM6</b>	PML12SS	<b>4PM6-S</b>
	3/4" - 14 NPTF	---	<b>4PM6-9<sup>1</sup></b>	---	---
	1" - 11 1/2 NPTF	---	<b>4PM8</b>	---	---

<sup>1</sup> steel/PTFE coating



steel



303 stainless