



Tuff-Lite™

Hose Shank x Female NPT Insert

Features:

- Nylon fittings should not be used with acid-based fertilizers, bromine, chlorine, fluorine, hydrochloric acid, iodine, nitric acid, phosphoric acid, sulfuric acid or xylene.
- nylon should not be used with compressed gas 

Hose Size	Female NPT	Nylon Part #
1/4"	1/4"	<b>TFS22</b>
1/4"	1/2"	<b>TFS42</b>
1/2"	1/2"	<b>TFS44</b>
3/4"	3/4"	<b>TFS66</b>



Female 45°SAE/37°JIC Swivel x Hose Barb

Feature:

- ball seat type

Hose Size	Female NPSM	Nylon Part #
1/4"	1/4"	<b>TF22</b>
3/8"	3/8"	<b>TF33</b>



Short Shank x Female NPSM Coupling

- sold in package quantities only
- shipped with a red vinyl washer (**TVW7**), replacement washers on page 242

Hose Shank	Female NPSM	Nylon Part #	Pkg Qty
1/4"	3/4"	<b>TCF62</b>	50
3/8"	3/4"	<b>TCF63</b>	50
1/2"	3/4"	<b>TCF64</b>	50
5/8"	3/4"	<b>TCF65</b>	50
3/4"	3/4"	<b>TCF66</b>	50

