

## SHD-Series Schrader Pneumatic Couplings

### Feature

- Interchanges with Parker Twist-Lock, Tomco Series-TL, Foster SHD

### Specifications

- Pressure rating: **300 PSI**
- Temperature range: **-40°F to 250°F (-40°C to 121°C)**

Operating pressure for couplings utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon® Quick Coupling cannot assume liability for misapplication of production resulting in equipment downtime, lost production, and/or personal injury, including death.



**E**

### Female Threaded Plugs

Body Size	Threads	Steel Part #
1/4"	1/8" – 27 NPT	SHD2F1
	1/4" – 18 NPT	SHD2F2
1/2"	3/8" – 18 NPT	SHD4F3




### Male Threaded Plugs

Body Size	Threads	Steel Part #
1/4"	1/8" – 27 NPT	SHD2M1
	1/4" – 18 NPT	SHD2M2
1/2"	3/8" – 18 NPT	SHD4M3
	1/2" – 14 NPT	SHD4M4



### Female Threaded Couplers

Body Size	Threads	Aluminum Part #
1/4"	1/4" – 18 NPT	2SHDF2
	3/8" – 18 NPT	2SHDF3
1/2"	3/8" – 18 NPT	4SHDF3
	1/2" – 14 NPT	4SHDF4
	3/4" – 14 NPT	4SHDF6



### Male Threaded Couplers

Body Size	Threads	Aluminum Part #
1/4"	1/4" – 18 NPT	2SHDM2
	3/8" – 18 NPT	2SHDM3
1/2"	3/8" – 18 NPT	4SHDM3
	1/2" – 14 NPT	4SHDM4

