

## Hydraulic Adapters – British Standard Pipe Parallel (BSPP)

### Male JIC 37° Flare x Male

**Specification**

- Pressure rating at 70°F (21°C)

Male JIC 37° Flare	Male BSPP	PSI	Zinc Plated Steel Part #
7/16" – 20	1/4" – 19	5000	B3800-4-4
9/16" – 18	3/8" – 19	4000	B3800-6-6
3/4" – 16	1/2" – 14	3000	B3800-8-8
1-1/16" – 12	3/4" – 14	2500	B3800-12-12
1-5/16" – 12	1" – 11	2000	B3800-16-16




### Male NPTF x Male

**Specification**

- Pressure rating at 70°F (21°C)

Male NPTF	Male BSPP	PSI	Zinc Plated Steel Part #
1/4" – 18	1/4" – 19	5000	B3401-4-4
3/8" – 18	3/8" – 19	4000	B3401-6-6
1/2" – 14	1/2" – 14	3000	B3401-8-8
3/4" – 14	3/4" – 14	2500	B3401-12-12
1" – 11-1/2	1" – 11	2000	B3401-16-16




### Female NPTF x Male

**Specification**

- Pressure rating at 70°F (21°C)

Female NPTF	Male BSPP	PSI	Zinc Plated Steel Part #
1/4" – 18	1/4" – 19	5000	B3455-4-4
3/8" – 18	3/8" – 19	4000	B3455-6-6
1/2" – 14	1/2" – 14	3000	B3455-8-8
3/4" – 14	3/4" – 14	2500	B3455-12-12
1" – 11-1/2	1" – 11	2000	B3455-16-16



### Male JIC 37° Flare x Male 90° Elbow

**Specification**

- Pressure rating at 70°F (21°C)

Male JIC 37° Flare	Male BSPP	PSI	Zinc Plated Steel Part #
7/16" – 20	1/4" – 19	5000	B3801-4-4
9/16" – 18	3/8" – 19	4000	B3801-6-6
3/4" – 16	1/2" – 14	3000	B3801-8-8
1-1/16" – 12	3/4" – 14	2500	B3801-12-12
1-5/16" – 12	1" – 11	2000	B3801-16-16



### Bonded Dowty Seal for British Thread

**Specification**

- Pressure rating at 70°F (21°C)

Size	Plated Carbon Steel with Nitrile Rubber O-ring Part #
1/4" – 19	BDS04
3/8" – 19	BDS06
1/2" – 14	BDS08
3/4" – 14	BDS12
1" – 11	BDS16

