





Η



	Sweepe	r Nozzle			
Thread Size	Discharge	Length	Bras	S	
	_		Previous Part #	Part #	
3/4" GHT	3/16"	1.47"	500SN2	PSN76	
Footuro	Flexible Wa	ater Nozzle	5		
 Feature Bends for ware 	ter flow, shuts o	ff when releas	sed		
Threa	d Size		Part #		
3/4"	GHT		8005		
 Features All metal bod Curved desig your hand 		• our of	ter Nozzle Built in flow control to reg water flow Locking feature to make e Large easy-turn dial		
	d Size		Part #		
	GHT		PNB75GHT		
 ThermoGuarc from heat and with heavy us Durable brass in extreme co 	d remains comf	ortable even	water stream 125 PSI to weather h Material Heavy-duty die-cast z 		
Threa	d Size		Part #		
3/4"	GHT		PHDN75		
Insulated Wa Features • Clip locks to any spray patters • Industrial strength nylon hand • Rubber handle guard • GHT thread on head • Heavy duty brass valve and a		n dle	le Specifications • For use with hot water up to 140°F (60°C		
Threa	d Size		Chrome Plated Zin Part #	с	
3/4"	GHT		SN75		
 Features Clip locks to a Easy squeeze 		n • Stair • Rubb	r le nless steel spring with lifetir per handle guard	ne packing	

Brass valve and dajasting ha	
Thread Size	Zinc Metallized Part #
3/4" GHT	CSN75

Twist Nozzles

Specification

• Maximum operating pressure 150 PSI (water only)

Thread Size	Length	Extruded Brass		
		Previous Part #	Part #	
3/4" GHT	4"		BTN75	
	4"		500AN41	
	6-3/4"	500-AN7	500AN71	
nported				

