Hammer Unions

400-Series

Applications
Used on manifold and line connections, pump, suction, and mud service

Feature

· Red sub, black nut

Specification

• Up to 4,000 PSI NSCWP (non-shock cold working pressure)

Size	Configuration	NSCWP (PSI)	Forged Steel Part #
2"	threaded	4000	HU400200
3"	threaded	4000	HU400300
4"	threaded	4000	HU400400

602-Series

Applications

• For use in mud, manifold service and truck mounting applications running water, oil or mud service

Features

- · Lip type seal ring minimizes fluid flow turbulence while creating a pressure seal
- Orange sub, black nut

Specification

• Up to 6,000 PSI NSCWP

Size	Configuration	NSCWP (PSI)	Forged Steel Part #
1"	threaded	6000	HU602100
2"	threaded	6000	HU602200
3"	threaded	6000	HU602300
	buttweld	6000	HU602300BW1
4"	threaded	6000	HU602400

¹ Buttweld ends are schedule 80

1002-Series

Applications

· For use in high pressure systems and truck mounting applications running water, oil or mud

Features

- · Lip type seal ring minimizes fluid flow turbulence while creating a pressure seal
- Blue sub, red nut

SpecificationUp to 10.000 PSI NSCWP

Size	Configuration	NSCWP (PSI)	Forged Steel Part #		
1"	threaded	10000	HU1002100		
2"	threaded	10000	HU1002200		
3"	threaded	10000	HU1002300		
	buttweld	10000	HU1002300BW1		
4"	threaded	10000	HU1002400		
	buttweld	10000	HU1002400BW1		

¹ Buttweld ends are schedule XXS



