

Model Number Breakdown: H 8 C SW 075

Туре	Body Pressure Class	Material	Body/End Construction	Size Code		Options
Forged ½" - 2" Bolted Bonnet: G = Globe W = Gate Forged ½" - 2" Welded Bonnet: H = Gate F = Globe Cast ≥ 2½" Bolted Bonnet: L = Gate J = Globe	Pressure Class 1 = CL 150 3 = CL 300 6 = CL 600 8 = CL 800 Y = CL 800 (Y pattern) A = CL 1500 (Y pattern)	C = A105 or A216WCB carbon steel S = A182 F316L or A351 CF8M stainless steel A = Alloy 20 H = Hastelloy® C276 M = Monel I = Inconel® 600 O = Special	SW = Socket weld SE = NPT SX = SW / NPT XS = SW / NPT XS = NPT / SW B4 = Butt weld - sch. 40 B8 = Butt weld - sch. 80 F1 = Class 150 RF sch. 40 F2 = Class 150 RF sch. 40 F3 = Class 300 RF sch. 40 F4 = Class 600 RF sch. 40 F7 = Class 600 RF sch. 80 B1 = Class 150 RF ball F/F B3 = Class 300 RF ball F/F R1 = Class 150 ring joint R3 = Class 300 ring joint R4 = Pipe end sch 40 P8 = Pipe end sch 40 P8 = Pipe end sch 80 TE = Tube end AE = Adapter end VC = VCR fitting OO = Special FS = Full port SW	050 = ½" 075 = ¾" 100 = 1" 150 = 1½" 200 = 2" 250 = 2½" 300 = 3" 400 = 4" 600 = 6" 800 = 8" 010 = 10" 012 = 12" 014 = 14" 016 = 16" 018 = 18" 020 = 20" 024 = 24"	Trim Packing Bellows Cleaning Other	A = Stellite® / Hastelloy® and Hastelloy® bellows and TFE packing; TFE/Hastelloy® gasket (standard for chlorine) B = Hastelloy® / Hastelloy® and Hastelloy® bellows and TFE packing; TFE/Hastelloy® gasket C = PCTFE soft seat (also referred to Kel-F® or Neoflon®) D = Stellite® / Stellite® D6 = Stellite® / Stellite® 316 stainless steel wedge/disk and stem E = TFE soft seat T## = ##API Trim number, if not Eagle standard F = TFE packing; TFE / 316 stainless steel gasket G = Inconel® 625 bellows replaces 321 stainless steel bellows H = Cleaning-Chlorine service I = Cleaning-Oxygen service / cryogenic service J = Cryogenic construction L = Seal Weld (bolted) bonnet M = Material certification required N = Actuator P = Special paint Q = Extra testing R = Special requirement - contact factory S = Special bolting T = Tagging
Inconel® is a registered trademark of Huntington, Alloys, Inc. Hastelloy® is a registered trademark of Haynes International, Inc. Stellite® is a registered trademark of Thermadyne, Inc. Kel-F® is a registered trademark of 3M Neoflon® is a registered trademark of Daikin Industries			FE = Full port SE FX = Full port SW x SE XF = Full port SE x SW			 U = Purge ports V = Electropolish required W = Non-standard face to face X = X-ray Y = Locking handle Z = NACE requirements

connect with us on



© 2019 DVCC