Data Sheet

Garden Hose Fittings





514

572

574

575

578

585

586

587

588

589

590

591

592

594

595

590-SS

591-SS

592-SS 593

514-SS

Garden Hose Fittings	
500	Garden Hose Accessory Products
501	Female Hose x Female Pipe - non swivel
501-SS	Female Hose x Female Pipe - non swivel, 303 SS
502	Female Hose x Female Pipe - swivel
502-SS	Female Hose x Female Pipe - swivel, 303 SS
503	Female Hose x Male Pipe - non swivel
503-SS	Female Hose x Male Pipe - non swivel, 303 SS
504	Female Hose x Male Pipe - swivel
504-SS	Female Hose x Male Pipe - swivel, 303 SS
506	Female Hose x Female Hose - swivel
507	Male Hose x Female Pipe
507-SS	Male Hose x Female Pipe - 303 SS
508	Male Hose x Male Pipe
508-SS	Male Hose x Male Pipe - 303 SS
509	Male Hose x Male Hose
509-SS	Male Hose x Male Hose - 303 SS
513	Hose Cap

Male Hose x Male Pipe x Female Pipe

Short Shank Female Swivel - round nut

Short Shank Female Swivel - hex nut

Garden Hose Female Swivel - 303 SS

Garden Hose Set (male and female swivel)

Long Shank Set (male and female swivel)

Lok-On Male

Lok-On Set

Lok-On Female

Garden Hose Mender

Short Shank Male

Garden Hose Male

Long Shank Male

Garden Hose Male - 303 SS Garden Hose Female Swivel

Long Shank Female Swivel

Male Hose x Male Pipe x Female Pipe - 303 SS

Short Shank Set (male and female swivel) - round nut

Short Shank Set (male and female swivel) - hex nut

Garden Hose Set (male and female swivel) - 303 SS

Compliances

- FED-STD-H28/10 NH, NPSH
- SAE J530, NPT, NPTF

Compatible Hoses

All Swan, Colorite, Flexon, Ames, Teknor Apex, and other designated water and garden hoses

Materials

- Brass fittings: alloy 360
- Brass forged accessories: alloy 370
- Brass cast accessories: alloy 3604
- Brass: alloy CA2745 or C46400 for Lead Free Brass (parts ending in LF)
- Stainless steel: 303 stainless steel
- Plating: optional electroless nickel
- Washers NBR, SBR, and FDA Black PVC Duro

Performance

- Temperature rating: 34°F to 195°F Pressure rating: 150 PSI maximum
- Exceptions:

500QCF:140°F 500BFP: 140°F - 100 PSI 500QCFV: 140°F 500GHV: 140°F - 100 PSI 500GHY: 140°F - 100 PSI 500QCSG: 140°F 500QCK: **140°F** 500GH4VBK: 120°F - 100 PSI 500QCKV: 140°F 500YCF: 140°F - 100 PSI 500YCZ: 100°F - 100 PSI

Vacuum - not rated

NOTE: Barbed fittings require a clamp(s) or crimped ferrule to secure the hose

Applications / Markets

Industrial, irrigation, landscape, marine, car wash, contractor, farm and ranch, parks, nurseries, golf course, dairy, restaurant, and brewery washdown

Strengths / Features

- Hex and round nut products
- Solid and swivel adapters
- Size range from 3/8" to 1" for most products
- 85 available products
- Special sizes, configurations, and thread specifications available on request

Price Advantage

Available Volume Discount Program

NOTE: Not intended for use in potable water systems unless using Lead Free products (parts ending in LF)

Dixon Brass

40 Chestnut Ave, Westmont, IL, 60559 ph: 800.323.4440 fx: 800.628.7259 dixonvalve.com

© 2023 DVCC • GHFDS_823