

Imported Brass Ball Valves

Application:

- for control of air, water, oil and gas in hose or pipe lines, for other services please contact Dixon®

Features:

- pressure rating: **600 PSI WOG**; **150 PSI** Working Steam Pressure
- forged brass body
- blow-out proof stems
- PTFE seat, seal and thrust washer
- chrome-plated brass ball and plated steel handle
- maximum temperature: **366°F (186°C)**
- Underwriters Listed

female NPT x female NPT



Size	Port	Brass Part #
1/4"	full	FBV25
3/8"	full	FBV38
1/2"	full	FBV50
3/4"	full	FBV75
1"	full	FBV100
1 1/4"	full	FBV125
1 1/2"	full	FBV150
2"	full	FBV200



female NPT x female NPT



Size	Port	Brass Part #
2 1/2"	full	FBV250
3"	full	FBV300
4"	full	FBV400

Imported Brass Ball Valve with Locking Handle

Application:

- for control of air, water, oil and gas in hose or pipe lines, for other services please contact Dixon®

Features:

- pressure ratings: **600 PSI WOG**; **150 PSI** Working Steam Pressure
- forged brass body
- blow-out proof stem
- PTFE seat, seal and thrust washer
- chrome-plated brass ball and plated steel handle
- maximum temperature: **366°F (186°C)**

Female NPT	Port	Brass Part #
1/2"	full	FBVL50
3/4"	full	FBVL75
1"	full	FBVL100
1 1/4"	full	FBVL125
1 1/2"	full	FBVL150
2"	full	FBVL200
2 1/2"	full	FBVL250
3"	full	FBVL300
4"	full	FBVL400

