Solution > (1) Global Cast Angle Valves Female Inlet

Features:

- NPT inlet thread only
- aluminum handwheel
- working pressure: 300 PSI at 70°F (21°C)
- New York City Board of Standards and Appeals, approval # MEA 54-07-E
 - available finishes:
 - cast (standard)
 - polished: -P
 - chrome: -C
 - minimum quantity for special thread, consult Dixon

Inlet Female NPT	Outlet	Cast Yellow DZR Brass Part #	Price/E	Wt. Lbs.
11⁄2"	1 ¹ / ₂ " male NST (NH)	AV150-I	\$110.00	4.10
21/2"	21/2" male NST (NH)	AV250-I	222.00	9.00
21/2"	21⁄2" CSA	AV250C-I	222.00	9.00
21⁄2"	21⁄2" WCT	AV250W-I	222.00	9.00
21/2"	21⁄2" BAT	AV250B-I	222.00	9.00
21⁄2"	21⁄2" QST	AV250Q-I	222.00	9.00

Grooved Inlet

Inlet	Outlet	Cast Yellow DZR Brass	Price/E	Wt.
Grooved	Male NST (NH)	Part #		Lbs.
21/2"	21⁄2"	AVG250F-I \$225.00		9.5

Inlet	Outlet	Cast Yellow DZR Brass	Price/E	Wt.
Grooved	Female NPT	Part #		Lbs.
21⁄2"	21⁄2"	AVGF250-I	\$225.00	9.5

Double Female

Features:NPT inlet ar

•


- NPT inlet and outlet onlyaluminum handwheel
- working pressure: 300 PSI at 70°F (21°C)
- New York City Board of Standards and Appeals, approval # MEA 54-07-E
 - available finish:
 - cast (standard)

polished = -P chrome = -C

Inlet Female NPT	Outlet Female NPT	Cast Yellow DZR Brass Part #	Price/E	Wt. Lbs.
1½"	11⁄2"	AVF150-I	\$110.00	3.66
21⁄2"	21⁄2"	AVF250-I	222.00	9.80

Dimensions

Size	А	В	C (closed)	C (open)	D	E	Wt. in Lbs.
1½"	4.13"	3.75"	6.80"	7.78"	2.25"	1.81"	4.4
21⁄2"	5.69"	5.00"	9.00"	10.72"	3.19"	2.59"	9.5



Ρ